

CAC-120 Fib COLOR ASSESSMENT CABINET CONTROL



KEY FEATURES

- Seven Individual Hour meter for each Tube
- Up to Seven Tubes Controlled Output
(F-CWF-UV-D65-TL84-TL83-N) :custom name and front design also available on demand:
- Hour meter records each second-minute-hour of tube life
- Secure hour meter reset function
- Cabinet total life meter
- All tube turn off at power fail return
- Latch function to run up to all tubes
- Single Touch for tube On/Off :previous tube automatically turn off, when new one selected:
- High Visibility Crystal Display
- Back Light for Poor Environment
- Touch Push and Splash Prof Front
- User Friendly Operation
- High Speed Micro-controller Based
- High Power back Connectors
- Accurate and Highly Stable Life Timer
- Tube Replacement alarm at 1800-Hours
- Easy replacement & Wiring
- Internal Self Diagnose System
- Low Cost, High Efficient
- Solid State Outputs
- Low Failure Rate

SPECIFICATIONS

Controller Series	CAC-120 Series	
Dimensions	225x100x70 mm , weight 700g (approximate)	
Panel Cutout	As Drawing No.: CAC-120DWC	
Terminal Connection	Wiring Included	
Power	185 to 250 VAC - 5VA maximum 50-60Hz	
Operating Environment	0 to 50°C (32° to 122°F), humidity: 10 to 90% RH, non-condensing	
Instrument Case	Flame-Retardant Fiber Front case (back open circuitry)	
Warm-up Time	Quickly	
Input	Display Resolution	1 Second
	Input Sample Rate	N/A
	Accuracy	± 0.2% / hour
	Impedance	N/A
	Measurement	N/A
Output	Electronic Blast	7 - Solid State Relay : 1.5A@250VAC
	Inductive	7 - Solid State Relay : 1A@250VAC