

CAC-120B COLOR ASSESSMENT CABINET CONTROL

KEY FEATURES

- ➔ Seven Individual Hour meter for each Tube
- ➔ Up to Seven Tubes Controlled Output
(F-CWF-UV-D65-TL84-TL83-N) :custom name and front design also available on demand:
- ➔ Hour meter records each second-minute-hour of tube life
- ➔ Secure hour meter reset function
- ➔ Cabinet total life meter
- ➔ All tube turn off at power fail return
- ➔ Latch function to run up to all tubes
- ➔ Single Touch for tube On/Off :previous tube automatically turn off, when new one selected:
- ➔ High Visibility Crystal Display
- ➔ Back Light for Poor Environment
- ➔ Touch Push and Splash Proof Front
- ➔ User Friendly Operation
- ➔ High Speed Micro-controller Based
- ➔ High Power back Connectors
- ➔ Accurate and Highly Stable Life Timer



- ➔ Tube Replacement alarm at 1800-Hours
- ➔ Standard panel dimension (96x96mm)
- ➔ Easy replacement & Wiring
- ➔ Internal Self Diagnose System
- ➔ Low Cost, High Efficient
- ➔ Solid State Outputs
- ➔ Low Failure Rate

SPECIFICATIONS

Controller Series	CAC-120B Series	
Dimensions	96x96x75 mm , weight 375g (approximate)	
Panel Cutout	91x91 mm (+/-0.3 mm)	
Terminal Connection	Screws accepting 16-24 AWG wires or 6.3 mm fork lug	
Power	185 to 250 VAC - 5VA maximum 50-60Hz	
Operating Environment	0 to 50°C (32° to 122°F), humidity: 10 to 90% RH, non-condensing	
Instrument Case	Flame-Retardant ABS plastic case	
Warm-up Time	Quickly	
Input	Display Resolution	1 Second
	Input Sample Rate	N/A
	Accuracy	± 0.2% / hour
	Impedance	N/A
	Measurement	N/A
Output	Electronic Blast	7 - Solid State Relay : 1.5A@250VAC
	Inductive	7 - Solid State Relay : 1.5A@250VAC